

12~24VDC

B14

ECE R65 LED BEACON



FEATURES

- Certified powerful ECE R65 performance in all colour.
- Aero-dynamic Smooth dome lens for best appearance.
- Multiple mounting styles for all vehicle applications.
- 12~24VDC Multi-Voltage Input.
- LEDs rated to 100,000 hours of operation.
- Non-volatile memory recalls last flash pattern used at power up.
- Multi-units synchronization in simultaneous or alternating flash.
- Reverse polarity protection.
- Weatherproof and vibration resistant design for external or internal use.

SPECIFICATIONS

Compliance: ECE R65(TA1; TB1; TR1); ECE R10; SAE J845; CA13; IPX5

Operating Voltage: 12~24VDC

No. of Warning Patterns: 11

LED Elements: 3W LED x 10pcs

Avg. Current: 1.7A @12.8VDC / 0.88A @24VDC (varies with flash pattern)

Max. Current: 3.3A @12.8VDC / 1.75A @24VDC

Avg. Power: 21 W (varies with flash pattern)

Max. Power: 42 W

Wires:

Magnetic Mount

- Single button cigar-plug: 300cm
- European cigar-plug: 250cm

Permanent Mount

- Red-Vcc : 40cm /15.74in (20AWG)
- Black-GND: 40cm /15.74in (20AWG)
- Yellow-Flash Patterns & Sync: 40cm /15.74in (20AWG)
- White-Phase: 40cm /15.74in (20AWG)

Fuse Rating : 5A

Synchronization: Up to 4 units

Storage Temperature: -40°C to +75°C

Operating Temperature: -30°C to +65°C

LED Colour: Red, Blue, Amber, White

Lens Colour: Red, Blue, Amber, Clear

ACCESSORIE

99-B014M01-000
B14 Branch Guard





99-B014X02-000
Rubber Wedge




DIMENSIONS

Permanent / Magnetic Mount



DIN Pole Mount



PART NO.

- **B014-1x238-000** ECE R65, Amber LED, Amber Lens (TA1)
- **B014-1x232-000** ECE R65, Blue LED, Blue Lens (TB1)
- **B014-1x234-000** ECE R65, Red LED, Red Lens (TR1)
- **B014-1x73A-000** ECE R10, Amber LED, Clear Lens
- **B014-1x73B-000** ECE R10, Blue LED, Clear Lens
- **B014-1x135-000** SAE, White LED, Amber Lens
- **B014-1x132-000** SAE, Blue LED, Blue Lens
- **B014-1x134-000** SAE, Red LED, Red Lens

Mounting style - replace x with the following:

- 1 = 3-Bolt Mount
- 2 = Magnetic Mount (straight cord with single button cigar-plug)
- 3 = DIN pole Mount
- 4 = Magnetic Mount (coiled cord with European cigar-plug)
- 5 = Power Magnet Mount (straight cord with single button cigar-plug)
- 6 = Power Magnet Mount (coiled cord with European cigar-plug)

FLASH PATTERN

FP#	FLASH PATTERNS	FP#	FLASH PATTERNS
1	Double [R65]	7	Quint [SAE]
2	Single [2Hz]	8	Mega
3	Quad [2Hz]	9	Ultra [SAE]
4	Single [SAE, CA13]	10	Single-Quad
5	Double [SAE]	11	Single H/L
6	Quad [SAE]		

*All approvals are based on actual model ordered.